

NEW, CONTINUATION, DIVISIONAL OR  
CONTINUATION-IN-PART APPLICATION  
UNDER 37 C.F.R. §1.53(b)

Attorney Docket No. 9624000001CPA

Express Mail Label No. EH293849897US

Date December 22, 1998

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Hon. Commissioner of Patents and Trademarks  
Washington, D. C. 20231

Sir:

Transmitted herewith for filing under 37 C.F.R. §1.53(b) is a patent application for IMAGE VIEWING  
DEVICE

identified by: ☐ First named inventor \_\_\_\_\_  
or ☒ Attorney Docket No. (see above)

1. Type of Application

- ☐ This application is a new (non-continuing) application.
- ☒ This application is a ☐ continuation / ☐ divisional / ☒ continuation-in-part of prior United States application No. 08/912,700, filed August 18, 1997.
- ☐ The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied, is considered part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

If for some reason applicant has not requested a sufficient extension of time in the parent application, and/or has not paid a sufficient fee for any necessary response in the parent application and/or for the extension of time necessary to prevent the abandonment of the parent application prior to the filing of this application, please consider this as a Request for an Extension for the required time period and/or authorization to charge our Deposit Account No. 08-0750 for any fee that may be due. THIS FORM IS BEING FILED IN TRIPLICATE: one copy for this application; one copy for use in connection with the Deposit Account (if applicable); and one copy for the above-mentioned parent application (if any extension of time is necessary).

2. Contents of Application

- a. Specification of 25 pages;
- ☐ A microfiche computer program (Appendix);
  - ☐ A nucleotide and/or amino acid sequence submission;
- ☐ Because the enclosed application is in a non-English language, a verified English translation ☐ is enclosed ☐ will be filed.
- ☐ Cancel original claims \_\_\_\_ of the prior application before calculating the filing fee. (At least one original independent claim must be retained for filing date purposes.)
- b. ☒ Drawings on seven (7) sheets;

Attorney Docket No. 9624000001CPA

Express Mail Label No. EH293849897US

Date December 22, 1998

- c. ☒ A signed Oath/Declaration ☒ is enclosed / ☐ will be filed in accordance with 37 C.F.R. §1.53(f).

The enclosed Oath/Declaration is ☐ newly executed / ☐ a copy from a prior application under 37 C.F.R. §1.63(d) / ☐ accompanied by a statement requesting the deletion of person(s) not inventors in the continuing application.

d. **Fees**

<b>FILING FEE</b>	Number	Number	Basic Fee
<b>CALCULATION</b>	Filed	Extra	Rate
Total Claims	24 - 20 =	4 ×	\$18.00 = 72.00
Independent Claims	1 - 3 =	0 ×	\$78.00 = 0
Multiple Dependent Claim(s) Used			\$260.00 = 0
FILING FEE - NON-SMALL ENTITY			862.00
FILING FEE - SMALL ENTITY: Reduction by 1/2			
<input type="checkbox"/> Verified Statement under 37 C.F.R. §1.27 is enclosed.			431.00
<input type="checkbox"/> Verified Statement filed in prior application.			
Assignment Recordal Fee (\$40.00)			0
37 C.F.R. §1.17(k) Fee (non-English application)			0
<b>TOTAL</b>			<b>\$431.00</b>

- ☐ A check is enclosed to cover the calculated fees. The Commissioner is hereby authorized to charge any additional fees that may be required, or credit any overpayment, to Deposit Account No. 08-0750. A duplicate copy of this document is enclosed.

- ☒ The calculated fees will be paid within the time allotted for completion of the filing requirements.

- ☐ The calculated fees are to be charged to Deposit Account No. 08-0750. The Commissioner is hereby authorized to charge any additional fees that may be required, or credit any overpayment, to said Deposit Account. A duplicate copy of this document is enclosed.

3. **Priority Information**

- ☐ **Foreign Priority:** Priority based on \_\_\_\_\_ Application No. \_\_\_\_\_, filed \_\_\_\_\_, is claimed.

- ☐ A copy of the above referenced priority document ☐ is enclosed / ☐ will be filed in due course, pursuant to 35 U.S.C. §119(a)-(d).

- ☐ **Provisional Application Priority:** Priority based on United States Provisional Application No. \_\_\_\_\_, filed \_\_\_\_\_, is claimed under 35 U.S.C. §119(e).

Attorney Docket No. 9624000001CPA  
Express Mail Label No. EH293849897US  
Date December 22, 1998


4. **Other Submissions**

- ☐ A Preliminary Amendment is enclosed.
- ☐ An Information Disclosure Statement, \_\_\_\_\_ sheets of PTO Form 1449, and \_\_\_\_\_ patent(s)/publications/documents are enclosed.
- ☐ A power of attorney
- ☐ is submitted ☐ with the new Oath/Declaration.
- ☐ is of record in the prior application and ☐ is in the original papers / ☐ a copy is enclosed.
- ☐ An Assignment of the invention
- ☐ is enclosed with a cover sheet pursuant to 37 C.F.R. §§3.11, 3.28 and 3.31.
- ☐ is of record in a prior application. The assignment is to \_\_\_\_\_, and is recorded at Reel \_\_\_\_\_, Frame(s) \_\_\_\_\_.
- ☐ An Establishment of Assignee's Right To Prosecute Application Under 37 C.F.R. §3.73(b), and Power Of Attorney is enclosed.
- ☒ An Express Mailing Certificate is enclosed.
- ☒ Other: an unexecuted Verified Statement Claiming Small Entity Status

Attention is directed to the fact that the correspondence address for this application is:

Harness, Dickey & Pierce, P.L.C.  
P.O. Box 828  
Bloomfield Hills, Michigan 48303  
(248) 641-1600.

Respectfully,



Preston H. Smirman  
Reg. No. 35,365

Date 12/22/98  
Harness, Dickey & Pierce, P.L.C.  
P.O. Box 828  
Bloomfield Hills, Michigan 48303  
(248) 641-1600

IMAGE VIEWING DEVICE

**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation-in-part application of U.S. Patent Application Serial No. 08/912,700 entitled "Camera for Covert Surveillance", filed August 18, 1997, pending, the entire specification of which is expressly incorporated herein by reference.

**FIELD OF THE INVENTION**

This invention relates generally to surveillance devices and photography, and more particularly to an image viewing device for producing and viewing high resolution fisheye images under various operational parameters and lighting conditions.

**BACKGROUND OF THE INVENTION**

The camera is the basic instrument of photography. In its simplest form, a camera comprises a light-tight box with a lens at one end, which forms an image of the subject on light-sensitive film at the other end. A pinhole maybe substituted for the lens (e.g., a pinhole camera, *camera obscura*); however, this approach generally produces an image of the subject that is not sharp (i.e., poor resolution).

With reference to Figure 1, there is shown a conventional camera 10, in accordance with the prior art. Nearly all modern cameras contain a glass

or plastic lens or lens system **12** to focus a sharp image of the subject onto the film **14**; a shutter **16** to control the length of time the film **14** is exposed, normally a fraction of a second; a viewfinder **18** to show the subject being photographed, and a mechanism (not shown) to hold the film and change film between exposures. A light-tight enclosure or housing **20** is also typically provided for protecting the film **14** from unintended exposure to the light. Many cameras include a lens aperture control (not shown) to regulate image brightness on the film. Advanced cameras may accept a variety of lenses for different photographic effects.

Cameras designed for still photography include, without limitation, the following types: box and other simple cameras, folding, 35-mm, reflex, press, view, instant picture, panoramic, electronic disk, underwater, aerial, stereo, medical, and document-copying or microfilm.

Cameras designed for action photography include, without limitation, the following types: videotape cameras, motion picture cameras, both conventional and high-speed, and television cameras - which are similar to photographic cameras but which use a light-sensitive electronic device instead of film.

Cameras have long been used for many purposes such as for surveillance, and especially covert surveillance. The availability of covert surveillance systems is of significant importance to certain groups, most especially the law enforcement and intelligence communities. The ability to detect and record images of subjects and events (especially those occurring in a interior portion of a room or a building) has permitted the gathering of

evidence and information which had previously been difficult or impossible to do.

However, initial surveillance systems were unsatisfactory in that they did not permit the entire room to be viewed simultaneously. Typically, these surveillance systems employed a camera having a conventional lens systems wherein the field of view allowed the imaging of a relatively small area, typically a square or rectangular area directly in front of the camera. Therefore, events that occurred either below, above, or to the left or right of the field of view of a conventional camera escaped detection and recording by the surveillance system.

With reference to Figure 2, there is shown a highly simplified conventional camera **22**, in accordance with the prior art. In this view, only the lens **24**, the film or image sensor **26**, and the housing **28** are illustrated. As light rays **L1**, **L2**, **L3**, and **L4** from an image enter the lens **24**, they are focused and strike the image sensor **26** (e.g., film, semiconductor imager, etc.). It should be noted that only four light rays are shown in this view for ease of illustration. However, as previously noted, the main disadvantage of the conventional camera is that there is a limited field of view. As a result, only a relatively small portion of the total potential field of view can be viewed and recorded at any one given time.

In an effort to enlarge the field of view of surveillance systems, it was suggested that a camera having lens system capable of producing a 180° field of view be employed. This 180° field of view produces what is generally

referred to as a "fisheye view." The term "fisheye view" refers to the fact that a fish sees a 180° image of the external world above water which is folded into a relatively narrow cone when it views the water surface from below. A fisheye view may be produced by a conventional fisheye lens, which is typically a very wide angle lens. The conventional fisheye lens magnifies the parts of the image near the focal point (e.g., center of the image) and simultaneously de-magnifies parts of the image that are far away from the focal point. When using such a conventional fisheye lens, there is no practical way for an individual or object to enter the room without being observed and recorded. Several models of conventional fisheye lenses that achieve at least a 180° field of view (including some that achieve a 220° field of view) are readily commercially available from Nikon, Inc (Nikon Product Numbers 1405 NAS, 1402 NAS, and 1910 NAS).

However, conventional fisheye lenses are generally large and bulky devices that project several inches away from the face of the camera housing, making them extremely difficult to easily conceal. In order to overcome this problem, it was suggested that a conventional fisheye lens camera be placed or mounted behind a hole or an aperture in a wall or other suitable opaque object, thus concealing the camera completely. However, conventional fisheye lenses would need a relatively large aperture in order to allow for a sufficiently large enough angle, thus defeating the purposing of concealing the camera behind the wall. Therefore, conventional fisheye lens cameras are unsuitable for covert surveillance purposes where it is intended to place the camera

behind a very small hole in a wall.

Therefore, there exists a need for an image viewing device that is easily concealable for covert surveillance uses but that is also capable of producing and viewing high resolution fisheye views under various operational parameters and lighting conditions.

### **SUMMARY OF THE INVENTION**

In accordance with one embodiment of the present invention, an image viewing device comprises a member having an area defining an aperture, the light rays from the image entering through the aperture; and an optical block comprised of a refractive material, the optical block being located adjacent to the aperture, the optical block being capable of compressing the light rays from the image that pass through the aperture so as to produce an image comprising at least a 180° field of view.

Further areas of applicability of the present invention will become apparent from the detailed description provided hereinafter. It should be understood however that the detailed description and specific examples, while indicating preferred embodiments of the invention, are intended for purposes of illustration only, since various changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from the detailed description.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

Figures 1 and 2 are cross-sectional views of prior art cameras;



Figure 3 is an exploded view of an image viewing device, in accordance with one aspect of the present invention;

Figures 4 and 4A are cross-sectional views of an image viewing device, in accordance with one aspect of the present invention;

5           Figure 5 is a cross-sectional view of an image viewing device with an optional image detection means associated therewith, in accordance with one aspect of the present invention;

10           Figure 6 is a partial cross-sectional view of an image viewing device with an optional cleaning means associated therewith, in accordance with one aspect of the present invention;

Figure 7 is an exploded view of an image viewing device with an optional image intensifier associated therewith, in accordance with one aspect of the present invention;

15           Figure 8 is a cross-sectional view of an image viewing device with an optional image intensifier associated therewith, in accordance with one aspect of the present invention;

Figure 9 is an exploded view of an image viewing device with an optional image intensifier and image detection means associated therewith, in accordance with one aspect of the present invention;

20           Figure 10 is an exploded view of an image viewing device with an optional lens associated therewith, in accordance with one aspect of the present invention;

Figure 11 is an exploded view of an image viewing device with an

optional color filter associated therewith, in accordance with one aspect of the present invention; and

Figure 12 is an exploded view of an image viewing device with an alternative optical block associated therewith, in accordance with one aspect of the present invention.

The same reference numerals refer to the same parts throughout the various Figures.

**DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT**

With reference to Figure 3, the image viewing device **30** is comprised primarily of two major components. The first component is a member **32** having an area defining an aperture **34** extending completely through the member **32** for allowing light rays to pass therethrough. The aperture **34** is preferably centered on the member **32**. Associated with the member **32** is the second major component, an optical block **36** which preferably has a diameter approximately equal to the member **32**. The exact configurations of the member **32** are not thought to be critical. In one embodiment, the member **32** is a round or oval cup-shaped device that receives a like-configured optical block **36**. In another configuration, the member **32** is substantially planar member (not shown) with the optical block **36** being received in a separate enclosure or housing (not shown). In yet another configuration, both the member **32** and the optical block **36** are received in a single housing or enclosure (not shown). The main consideration is that once the member **32**

and the optical block **36** are brought together into operational engagement, the optical block **36** must be contained in a light-tight enclosure. This is necessary to prevent the light rays that pass through the aperture **34** and into the optical block **36** from escaping, thus rendering any image unviewable.

5           With reference to Figure 4, an image viewing device **40** is primarily comprised of a housing **42**, an aperture **44** (preferably centrally located on a surface of the housing **42** facing the subject to be imaged), and an optical block **46** (preferably filling or substantially filling the entire interior area of the housing **42**. It should be noted that the configuration of the housing **42** is for illustrative purposes only. For example, the housing **42** could be configured to include a triangular portion tapering towards the aperture **44**, thus reducing the amount of material needed for the housing **42** and the optical block **46** (see Figure 4A). An optional viewfinder (not shown) could be provided on the surface of the housing **42** opposed from the aperture **44**. However, it may be difficult for the naked eye to clearly make out the image, unless the rear surface of the optical block **46** is treated (e.g., sanding). However, additional optional devices may be used in conjunction with the present invention to enhance the resolution and viewability of the fisheye image generated. As light rays **L5** and **L6** from an image enter the aperture **44**, they are compressed in angle by the optical block **46** to form the previously discussed fisheye image on the surface of the optical block opposed from the aperture **44**. It should be noted that only two light rays are shown in this view for ease of illustration. However, as compared with conventional cameras, the main

advantage of the present invention is that there is a much greater field of view. As a result, a relatively large portion (i.e., at least 180°) of the total potential field of view can be viewed and recorded at any one given time.

5 The present invention comprises an improved image viewing device which may be as small as may operate through a 100 micron hole or aperture (hence the term "pinhole" which refers to the very small size holes or apertures employed). The smallest possible hole is desirable for concealment, but for visible light, 100 microns is as small as can be used without suffering image degradation due to optical diffraction. The exact equation for the optimum  
10 pinhole diameter is given by:

$$D = \sqrt{L\lambda}$$

wherein D is the pinhole diameter, L is the distance from the pinhole to the  
15 photo receptor surface, and  $\lambda$  is the wavelength of the light used. The 100 micron pinhole was designed using the specific equation given above for visible light at 5000 angstroms and a pinhole to film distance of 2 centimeters. The 100 micron pinhole is merely illustrative of one embodiment of the present invention, and is not meant to limit the scope of the present invention. A larger  
20 pinhole may be used to increase the light gathering power and improve resolution by reducing diffraction, but has the dual disadvantages of reduction of concealment and optical complexity. Preferably the pinhole has a diameter from about 100 microns to about 1 centimeter.

In order to capture and record the fisheye image, an optional image detection means is preferably associated with image viewing device of the present invention. With reference to Figure 5, an image viewing device **50** is similar to the one illustrated in Fig. 4; however, the difference lies in the use of an optional image detection means **52**. The image detection means **52** of the present invention can be either photographic film (e.g., motion picture camera, still photographic camera), or a semiconductor element (e.g., videotape camera), or any other type of camera whose purpose is to capture and record images. For example, the rear portion of the image viewing device **50** could be adapted to receive a conventional camera (e.g., clamps, clips, threaded screw, etc.). Additionally, an optional viewfinder (not shown) can be provided to allow an operator to view the fisheye image generated before actuating the image detection means **52**.

With reference to Figure 6, an image viewing device **50** is similar to the one shown in Figure 5; however, the difference lies in the use of an optional cleaning means **54**. Because debris (e.g., snow, ice, etc.) and dust may form about the aperture **44** and on the surface of the optical block **46** closest to the aperture **44**, the cleaning means **54** can deliver, by way of a non-limiting example, a measured amount of compressed gas or air through a conduit **56** outwardly toward the area surrounding the aperture **44** in order to loosen and remove any debris therefrom. Although only one conduit **56** is shown, it should be noted that a plurality of these structures may be employed to more efficaciously loosen and remove debris. Therefore, the image viewing device

of the present invention can be programmed to be self-cleaning by the periodic application of pressurized gas or air about the aperture **44**.

The image viewing device of the present invention operates at very low light levels, and also operates in the infrared. The image produced can be rectified and zoomed using available computer technology, such as digital image processing technology. As an example, Interactive Pictures Corporation (Oak Ridge, Tennessee) markets a software package to perform this function. The image viewing device of the present invention is simple, compact, rugged, and may be battery-powered. The image viewing device is capable of having full color capability at extremely low light levels. In addition, a new technology increases the resolution of the image as it is enlarged during zooming. The loss of resolution on zooming closer (loss of pixels) was a major criticism for the zooming system used on earlier 180° non-pinhole cameras.

One feature of the present invention was to provide the smallest practical aperture for covert surveillance system applications of the image viewing device of the present invention. The limitation is that if the aperture is too large, the image blurs because of the hole size. If the aperture is too small, the image also blurs due to the property of light known as diffraction. As previously noted, the optimum aperture size, i.e., not too large and not too small, is about 100 microns. This is in practical terms about one tenth the diameter of a pencil point. Thus, if one wishes to conceal the image viewing device behind an opaque object (e.g., a wall), a hole must be placed in that

object approximately equal to the aperture size of the image viewing device. Normally, if the surface containing the hole is placed in front of an observer, he or she will be unable to locate it.

Another feature of the present invention was to provide a fisheye image  
5 that is easily visible with a high degree of resolution. Previous pinhole cameras suffer from insufficient light entering the lens, i.e. the pinhole is just too small. The present invention has solved this problem by using an image intensifier to enhance the image. With reference to Figure 7, an image viewing  
10 device **30** is similar to the one shown in Fig. 3; however, the difference lies in the use of an optional image intensifier **58**. The image intensifier **58** is generally required because the amount of light passing through a 100 micron pinhole, even under optimum lighting conditions, is too low to produce an acceptable image without intensification. The image intensifier **58** operates as follows: visible or infrared light strikes an electron emitting screen. These  
15 electrons are accelerated (given much energy) so that they then strike a fluorescent screen, which then in turn emits much more visible light than that originally striking the electron emitting screen. A thin metal film situated between the electron emitting screen and the fluorescent screen transmits electrons, but not light, thus preventing optical feedback. Preferably, the  
20 image intensifier **58** has a self-contained power source, such as a battery (not shown). It has been observed that currently available image intensifiers actually work so well that the image viewing device of the present invention works at extremely low light levels (i.e., approximately 80 times better than the

unaided naked eye) at which human vision becomes impaired. In addition, the image intensifiers employed are sensitive to the near-infrared (i.e., 600 to 1000 angstroms). Human eyes cannot see in these wavelengths, so an interior room could be illuminated with infrared radiation to allow the image viewing device of the present invention to operate in a room that appears to be totally dark. An additional advantage of using the image intensifier **58** is that it can be optically coupled to the optical block **36** with glue, grease, or just contact pressure. In this way, the fisheye image never really leaves the optical block **36**, but is transmitted to the image intensifier **58** without loss. With reference to Figure 8, a non-limiting example of an image viewing device **50**, similar to the one shown in Fig. 4, along with an optional image intensifier **58** is shown. With reference to Figure 9, a non-limiting example of an image viewing device **50**, similar to the one shown in Fig. 5, along with an image intensifier **58** is shown.

Image intensifiers are readily commercially available from Edmund Scientific Company (Barrington, New Jersey). An intensification of 50,000 times is claimed by certain image intensifiers, giving the camera of the present invention a theoretical improvement of 80 times over the unaided naked human eye. The image intensifier used in the present invention can multiply the light emitted by the image by a magnitude of 10,000 times.

With respect to the operation of the image viewing device of the present invention, light rays from an image enter through the aperture, and upon entering the aperture, they are focused through the optical or dielectric block,



which can be comprised of glass or plastic. The optical block should be made of a material which has a high index of refraction (preferably more than about 1, and still more preferably from about 1.5 to about 4), and that is transparent to the radiation being used. Glass or plastic is preferable for visible light.

5 Silicon is preferable for the infrared, where the camera can be used to detect people in total darkness by body heat radiation alone. Summarizing, the optical block may be comprised of plastic, glass, refractive minerals such as quartz, materials transparent to infrared light such as silicon or germanium, and refractive liquids such as water. The optical block may be optically  
10 coupled by an optional interface or optical coupler (not shown) to the optional image intensifier. The optical coupler can comprise glue, pressure, or any other suitable material or device.

Referring now to Figure 10, an image view device **40**, is similar to the one shown in Fig. 4; however, the difference lies in the use of an optional lens  
15 **60**, which is placed in front of aperture **44**. The composition of lens **60** (actually a flat plate of about 10 times the aperture **44** diameter and a thickness about equal to the aperture **44** diameter) is of the same optical properties and material as the optical block **46**. Alternatively, lens **60** could be harder than the material of the optical block **46** to resist wear and abrasion.  
20 The object of lens **60** is to improve light transmission through the aperture **44**. However, the self-cleaning properties of the pressurized aperture **44** are lost due to the placement and location of lens **60**. Note that lens **60** must be in physical contact with the optical block **46** to get the desired improvement. The

placement of lens **60** allows for better viewing of the image to be produced by slightly improving the image at the edges. Additionally, this lens design is capable of producing field of view images greater than 180° and up to about 220°.

5           Another feature of the present invention is the ability to recover the color content of the fisheye image. Image intensifiers transmit the image by electrons, and thus lose the color content of the image. The intensified image is generally displayed as a green monochrome. Thus each green monochrome image from the image intensifier is viewed with a monochromatic  
10 video camera and transmitted to a recording computer. If a computer is being used to store and rectify the image data, with the information that it really is a red, yellow, or blue image, the computer reconstructs the image in natural color.

          The present invention has corrected this color content loss problem by  
15 placing an electrically tuned color filter behind the aperture and being optically coupled to the optical block, of course. With reference to Figure 11, an image viewing device **50**, is similar to the one shown in Fig. 9; however, the difference lies in the use of an electrically tuned color filter **62** (Displaytech, Boulder, Colorado). Preferably, the color filter **62** is disposed in a recess **46A**  
20 on the surface of the optical block **46** so as to be coplanar with the surface of the optical block **46**. Preferably, a control system **64** is in electrical communication with the color filter **62** so as to be able to control the operation of the color filter **62**. Additionally, optional components such as, but not limited

to, video cameras (not shown) and black and white video viewers (not shown) may be employed.

By way of a non-limiting example, several color filters may be electrically connected to the control system. When the proper voltages are applied to each color filter, the filters restrict the spectral range by eliminating certain wavelengths of visible light. For example, a red filter will absorb green and blue light, leaving only red light to transmit. If the same voltages are applied to each filter, they transmit the same color. Thus, for example, the first color filter admits green to the intensifier. At a viewing screen, a black and white image that represents green is displayed. The operator views this image through the second color filter to see a green image. The colors are then cycled to produce a full color image in the eye. The color filters can be solid state tunable color filters.

Another feature of the present invention is to preserve the resolution of the image as you zoom in on a subject. The former technique used in electrical zooming simply used a computer to expand a part of the image. This expansion is simply spreading the obtained information over a larger area, and thus the image just gets fuzzy or unresolved. This loss of resolution was considered to be a major defect of previous pinhole camera systems. The present invention has corrected the zooming loss of resolution in two ways. First, the present invention employs a system that electrically (not mechanically) expands the image on a given image chip. The same company which also produces the electrically switchable color filters (Displaytech,

Boulder, Colorado) also manufactures an electrically operable polarized light rotator. Thus, you can have light pass through a polarizer, and rotate the plane of polarization by ninety degrees. Then, a thin slab of the mineral calcite is placed across the optical path. The material does not have to be only calcite; it can be any other suitable transparent, doubly-refracting material. However, calcite is double refracting, so when the plane of polarization is rotated, the image moves sideways. Presently, a video camera recording chip is made of a finite number of pixels that are separated by dead space. In other words, the chip is only looking at about 1/4 of the image. If one were to take one image, store it in the computer, move the image a 1/2 pixel spacing, and take a second image, we have doubled the amount of information received, and a recording computer can enhance the image. By repeating this process in several directions, the image can be further enhanced. Thus, more information is gathered on a single pickup chip at the cost of slowing down the system response time.

A second technique is provided by using a second product from Displaytech (Boulder, Colorado), that being an electrically operated, non-mechanical shutter. Optionally, a semitransparent beamsplitter on each leg which has a separate electro-optical shutter can also be employed. By leg, it means two or more optical paths, created by optical beamsplitters, and chosen by opening or closing possible optical shutters. However, it should be noted that the optical shutters may be unnecessary, because one channel can be activated by simply turning off or on the appropriate computer recording chip.

When you wish to have the full image, the electro-optical shutter directs the full image to one computer vision chip. If you wish to zoom in on a part of the image, this shutter is closed, and another is opened that views only part of the image. This fraction of the image is viewed by a complete chip, so that even  
5 if the image is enlarged, the resolution remains the same. The process can go through several stages, increasing the resolution without image degradation. The basic problem is that zooming occurs in discrete stages, but a computer can be adjusted to smooth and overlap the transitions.

In an alternative embodiment, the present invention has eliminated the  
10 image intensifier and loss of color information, and has improved the resolution of the image at the cost of expanding the aperture by a factor of 20. The alternative embodiment, however, still maintains the 180° field of view. The aperture is now about the size of a thick pencil lead, i.e., 2000 angstroms. With the larger pinhole, the alternative embodiment employs a specially  
15 designed lens located behind the aperture to focus the light and greatly reduce the loss of resolution by diffraction. This configuration allows the light to escape and acts as a lens to focus light on the image detection means. If the surface of the lens is approximately normal to the path of the light ray, it can pass through without being reflected. With reference to Figure 12, an image  
20 viewing device **100** is comprised of two major components: (1) a member **102** with an area defining aperture **104** extending completely through the member **102**; and (2) an optical block **106** that is intended to function both as an image compressor and as a lens. The optical block **106** comprises a specially

designed dielectric or optical block which is curved on one side and which fills almost the entire interior area of the enclosure (not shown). The optical block 106 must have a spherical or parabolic surface facing the image detection means (not shown) such that two conditions are satisfied: (1) the surface must be approximately normal to the light path inside the optical block 106 so that light may escape and not be internally reflected; and (2) the surface of the optical block 106 acts as a convex lens and focuses the parallel light rays inside the optical block 106 onto the image detection means (not shown) outside the optical block 106. What is meant by the term "filling almost the entire camera" is that the size of the optical block 106 and the size of the airspace between the optical block 106 and the image detection means (not shown) are balanced to produce the proper sized, in-focus image on the image detection means (not shown). As an example, an approximate calculation calls for the optical block 106 to fill about half of the space inside the enclosure (not shown) to achieve the desired result. This lens design is not color corrected at present, so the image, when viewed by the naked eye, shows color fringing. However, this color fringing may be easily corrected with a computer.

While preferred embodiments of the present invention have been shown and described, it will be understood that there is no intent to limit the invention by such disclosure, but rather, it is intended to cover all modifications and alternate embodiments falling within the spirit and scope of the invention as defined in the appended claims.

What is claimed is:

1. An image viewing device, comprising:  
a member having an area defining an aperture, the light rays from the image entering through the aperture; and  
an optical block comprised of a refractive material, the optical block being located adjacent to the aperture, the optical block being capable of compressing the light rays from the image that pass through the aperture so as to produce an image comprising at least a 180° field of view.
- 5 2. The image viewing device according to claim 1, wherein the optical block has a substantially flat surface facing towards the aperture.
3. The image viewing device according to claim 2, wherein the optical block has a substantially parabolic surface opposite the flat surface.
4. The image viewing device according to claim 2, wherein the optical block has a substantially spherical surface opposite the flat surface.
5. The image viewing device according to claim 1, wherein the optical block abuts the member having an area defining an aperture.

6 The image viewing device according to claim 1, wherein an area defining a gap is located between the optical block and the member having an area defining an aperture.

7. The image viewing device of claim 1, further comprising a housing for receiving the optical block, wherein the housing is substantially light tight.

8. The image viewing device of claim 1, further comprising an image detection means, the optical block being located between the aperture and the image detection means, the image detection means being capable of viewing and recording the image produced by the optical block.

9. The image viewing device according to claim 1, further comprising an image intensifying means for intensifying the image produced by the optical block.

10. The image viewing device according to claim 9, further comprising a viewing means for viewing the image produced by either the optical block or the image intensifying means.



**HDP DOCKET 9624-000001CPA**

11. The image viewing device according to claim 9, further comprising a recording means for recording the image produced by either the optical block or the image intensifying means.

12. The image viewing device according to claim 9, further comprising a coupling means for optically coupling the optical block to the image intensifying means.

13. The image viewing device according to claim 1, further comprising a cleaning means for cleaning debris from either the aperture or the surface of the optical block facing towards the aperture.

14. The image viewing device according to claim 11, wherein the cleaning means comprises a selectively operable source of compressed air.

15. The image viewing device according to claim 1, further comprising a color filter means for selectively filtering wavelengths of visible light, the color filter means being in proximity to the optical block.

16. The image viewing device according to claim 1, wherein the optical block has an index of refraction in the range of more than about 1.

**HDP DOCKET 9624-000001CPA**

17. The image viewing device according to claim 1, wherein the optical block has an index of refraction in the range of about 1.5 to about 4.

18. The image viewing device according to claim 1, wherein the aperture has a diameter in the range of about 100 microns to about 1 centimeter.

19. The image viewing device according to claim 1, wherein the optical block is comprised of materials selected from the group consisting of plastic, glass, refractive minerals, quartz, materials transparent to infrared light, silicon, germanium, refractive liquids, water, and combinations thereof.

20. The image viewing device according to claim 1, wherein the image detection means is selected from the group consisting of photographic film, videotape detector chip, motion picture film, and combinations thereof.

21. The image viewing device according to claim 1, wherein a color image is produced.

22. The image viewing device according to claim 1, wherein a monochromatic image is produced.

**HDP DOCKET 9624-000001CPA**

23. The image viewing device according to claim 1, wherein a black and white image is produced.

24. The image viewing device according to claim 1, wherein a portion of the optical block extends through the aperture, the portion of the optical block extending through the aperture focusing the incoming light rays from the image.

**ABSTRACT**

An image viewing device is described which is capable of producing images comprising at least a 180° field of view, also referred to as fisheye images. The device employs an extremely small aperture in conjunction with an optical block comprised of a refractive material. The light rays from an image pass through the aperture whereupon they are compressed in angle by the optical block to produce the fisheye image. An optional image intensifier may be employed to enhance the image produced by the optical block. Additionally, optional filters, viewers, and recording devices may be employed to enhance the image produced as well as to provide a permanent record of any images produced. The image viewing device is capable of producing high resolution color, black and white, and monochromatic fisheye images under various weather and lighting conditions.




Fig. 1  
Prior Art




Fig. 2  
Prior Art

09218753 122298

Fig. 3





Fig. 4




Fig. 4A

09218763.122238  
8622221 E928T260




Fig. 5





Fig. 6

09218763 122298



32 32 30

52

55



09218763 12298 86222T 8928T260




Fig. 8




Fig. 9

TRANSPARENT  
DIELECTRIC  
INSERT FOR  
PINHOLE





Fig. 10



TRANSPARENT  
DIELECTRIC BLOCK  
TO COMPRESS IMAGE

09218763.12298  
86222T E9787260




Fig. 11




Fig. 12

**DECLARATION AND POWER OF ATTORNEY**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

**IMAGE VIEWING DEVICE**

the specification of which (check one)

☒ is attached hereto.

☐ was filed on \_\_\_\_\_ as Application  
Serial No. \_\_\_\_\_ and was amended on  
\_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application or to the patentability of the invention claimed therein in accordance with Title 37, Code of Federal Regulations, section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, section 119(a)-(d) of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

**PRIOR FOREIGN APPLICATION(S)**

			Priority Claim	
			Yes	No
_____ (Number)	_____ (Country)	_____ (Day/Month/Year filed)		
_____ (Number)	_____ (Country)	_____ (Day/Month/Year filed)	Yes	No
_____ (Number)	_____ (Country)	_____ (Day/Month/Year filed)	Yes	No

09218763.12299  
09218763.12299

## DECLARATION AND POWER OF ATTORNEY

I hereby claim the benefit under Title 35, United States Code, §119(e) of any United States Provisional application(s) listed below:

### PRIOR PROVISIONAL APPLICATIONS

\_\_\_\_\_  
(application serial number)

\_\_\_\_\_  
(Month / Day / Year filed)

\_\_\_\_\_  
(application serial number)

\_\_\_\_\_  
(Month / Day / Year filed)

I hereby claim the benefit under Title 35, United States Code, section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

Application Serial No.	Filing Date	Status - patented, pending, abandoned
<u>08/912,700</u>	<u>August 18, 1997</u>	<u>Pending</u>
_____	_____	_____
_____	_____	_____
_____	_____	_____

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

I hereby appoint Michael P. Brennan, Reg. No. 30,612, Preston H. Smirman, 35,365 and each principal, attorney of counsel, associate and employee of Harness, Dickey & Pierce, P.L.C., who is a registered Patent Attorney, my attorney with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith. I request the Patent and Trademark Office to direct all correspondence and telephone calls relative to this application to Harness, Dickey & Pierce, P.L.C., P. O. Box 828, Bloomfield Hills, Michigan 48303 (248) 641-1600.

Full name of sole or first inventor: Igor Alexeff

Inventor's signature: \_\_\_\_\_

Date: \_\_\_\_\_

Residence: 2790 Oak Ridge Turnpike, Oak Ridge, Tennessee 37830

Citizenship: United States of America

Post Office Address: Same as above

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

Group Art Unit:  
Examiner:  
Inventor(s): Igor Alexeff  
Serial Number:  
Filed:  
For: IMAGE VIEWING DEVICE

Patent No.  
Issued:

**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS  
(37 CFR 1.9(f) AND 1.27(b)) - INDEPENDENT INVENTOR**

As a below named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees under section 41(a) and (b) of Title 35, United States Code, to the Patent and Trademark Office with regard to the invention described in

- ☒ the specification filed herewith.  
☐ the application whose serial number is set forth above.  
☐ the patent set forth above.

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not likewise be classified as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b)).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Signature \_\_\_\_\_  
(Typed Name) Igor Alexeff

Date \_\_\_\_\_

09218763-12298